



Illustrative picture

**SPECIFICS**

<i>Description</i>	Product type	WALL SOCKETS
	Article code	<b>RS6421</b>
	Commercial Series	Box with sockets

<i>General Data</i>	Poles	N°	3P+N+E	Type of material	Nylon / Abs
	Current	A	32	Dimensional stability	°C -25 / +70
	Voltage	V~	200/346-240/415	Resistance glow wire test	°C +650 / +850
	Degree of protection	IP	44	Working temperature	°C , -25 + 55
	Impact Resistance	IK	8	Weight	kg 1,43
	Insulation Resistance	MΩ	>10		
	Dimensions LxDxH	cm	13,5X20X25		

  

Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 50250	2014/35/UE
------------------	--------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	1,43
	Package innerbox		5	7,85
	Packaging			



Reg. A.E.E n° IT17100000010057

CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Rev	Date	Technical Manager
01	7/1/20	<i>Romano Rosi</i>