

LOGO! TD text display, 6-line, 3 background colors, 2 Ethernet ports, installation accessories for LOGO! 8



Figure similar

| General information | |
|--|-------------------------------------|
| Product type designation | Text display |
| Suitability for use | Can be used with LOGO! 8 and higher |
| Display | |
| Design of display | FSTN |
| Line display | |
| <ul style="list-style-type: none"> Number of lines | 6 |
| <ul style="list-style-type: none"> Number of characters per line | 20 |
| Backlighting | |
| <ul style="list-style-type: none"> Type of backlighting | LED |
| Control elements | |
| Keyboard fonts | |
| <ul style="list-style-type: none"> System keys | Yes |
| <ul style="list-style-type: none"> — Number of configurable system keys | 0 |
| <ul style="list-style-type: none"> alphanumeric keyboard | No |
| Installation type/mounting | |
| Wall mounting/direct mounting | No |
| Supply voltage | |
| Type of supply voltage | AC/DC |
| Rated value (DC) | 12 V; 12/24 V DC, 24 V AC |
| Power loss | |
| Power loss, typ. | 1.8 W; At 24 V DC |
| Interrupts/diagnostics/status information | |
| Diagnostics function | No |
| Degree and class of protection | |
| IP (at the front) | IP65 |
| Standards, approvals, certificates | |
| CE mark | Yes |
| UL approval | Yes |
| FM approval | Yes |
| KC approval | Yes |
| Marine approval | |
| <ul style="list-style-type: none"> American Bureau of Shipping (ABS) | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> min. | -20 °C; No condensation |
| <ul style="list-style-type: none"> max. | 55 °C |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> min. | -40 °C |

| | |
|--|--|
| • max. | 70 °C |
| Altitude during operation relating to sea level | |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m) |
| configuration / header | |
| Configuration software | |
| • Configuration tool | LOGO! Soft Comfort V8 |
| Accessories | |
| belongs to product | LOGO! |
| Mechanics/material | |
| Design of housing | plastic |
| Dimensions | |
| Width | 128.2 mm |
| Height | 86 mm |
| Depth | 38.7 mm |
| Overall depth | 38.7 mm |
| Weights | |
| Weight, approx. | 220 g |
| Scope of supply | |
| Delivery quantity in pieces | 1 |

last modified: 3/12/2024 